DATA SHEET SL-1046X

sentinel vehicle lighting

LED directional pad warning light

Super low profile

88 x 30 x 6.6mm

Multivoltage 10-30Vdc

IP67

3 x high power diodes

ECE Reg 10: E6 10R 050652

LED directional pad warning light



Part number

SL-10461	LED directional pad, amber
SL-10462	LED directional pad, red
SL-10463	LED directional pad, blue
SL-10464	LED directional pad, white
SL-10469	Mounting bracket

Materials Lens: Base:

protection:

Warranty:

Specifications

LEDs:

Functions:

Certifications:

Dimensions:

Operating range:

Voltage:

IP rating:

Polycarbonate

Aluminium

Yes

3 years

Operating temperature:	-30°C to +65°C
Mounting:	Self-adhesive pad mount or screw mount
Wiring:	20cm long insulated wires, 24AWG White = power Black = ground Brown = synchronisation & flash patterns
Flash patterns:	12 selectable flash patterns, including steady burn
Synchronisation:	Multiple units can be synchronised to flash simultaneously or alternately
Current draw:	Avg 0.27A @12VDC / 0.14A @24VDC Max 0.54A @12VDC / 0.27A @24VDC
Power rating:	Avg power: 3.25W (varies with flash pattern) Max power: 6.5W
Reverse polarity	Yes